

PTZOPTICS Broadcast PTZ Camera Controller

Model Number:
PT-BRDCSTR-P

<http://ptzoptics.com/broadcast-ptz-camera-controller/>

The PTZOptics PT-BRDCSTR-P is a broadcast camera control system that supports Panasonic handheld-broadcast camcorders. Achieve full speed remote PTZ control with intelligent soft start and stop control. Feel safe with our built-in voltage control regulator for power protection.

KEY FEATURES

- Supports Panasonic Cameras*
- Supports VISCA, Pelco-P & Pelco-D control protocols
- Full speed P/T/Z control with intelligent start/stop
- Accurate pinpoint pan, tilt, and zoom positioning
- Up to 255 Presets
- Supports wall and tripod mounting
- Low Noise

***Others supported
(Inquire with make + model)**



WHAT'S IN THE BOX

- Camera Controller
- 19V DC Power Supply + Cord
- Instruction Manual
- 2.5mm/3.5mm "Y" Camera Control Cable
- Focus wheel + Bracket
- 1/4-20 camera tripod mounting bracket
- Tools (for adjustment)
- Wall & Tripod Mounting Screws

Supports Camera Types

Panasonic Models: AG-HPX173MC, AG-HPX260MC, AG-HPX265MC, AJ-PX285MC, AJ-PX298MC, AG-HVX200MC, AG-HMC153MC, AG-HVX203AMC, AG-AF103A, AG-AC130A, AG-AC160A, AG-AC90AMC
Most models with the remote lens control jack (2.5mm zoom) (3.5mm focus iris)

Supported Control Protocols

VISCA, Pelco-D, Pelco-P
Max System addressable: 7
Can mix camera types in same control network

Pan & Tilt Movement

Rotation Range 280° (-80° to 200°)
Rotation Speed Level: .01 ~25°/S; Vertical:0.1~20°/S
Tilt Range 90° total (±45° or 90 to 0° or 0 to -90 or -45 to -135)
Presets 255 Presets

Additional Support

Remote Camera Power Switch	Supported
Integrated Camera Power Supply	(over - voltage, under - voltage & over - current protection)
Controller Distance	3900 FT Max (1200m Max.)
Max Side Load:	11 lbs (5kg)
Max Top Load:	6.6 lbs (3kg)
Control Interface	RS-232, RS-422, RS-485
Control Network	Single Controller - Multi Camera Multi Controller - Single Camera Multi Controller - Multi Camera











Electrical Index

Power Supply	19V DC/4.75A (15W Consumption w/o camera)
Input Voltage	120VAC Max 1.6A







Physical Specifications

Dimensions W x D x H	8.8" x 6.44" x 9.94" (226mm x 164 x 253)
Weight	9.7 lbs. (4.1kg)
Operating Temp:	32°F to 104°F (0°C to 40°C)
Storage Temp:	-4°F to 140°F (-20°C to 60°C)








Product Line

	PT12X-SDI-GY-G2		PT12X-SDI-WH-G2	1080p PTZ camera, 12X optical zoom, 3G-SDI, HDMI, IP Streaming
	PT12X-USB-GY-G2		PT12X-USB-WH-G2	1080p PTZ camera, 12X optical zoom, USB3.0, HDMI, IP Streaming
	PT20X-SDI-GY-G2		PT20X-SDI-WH-G2	1080p PTZ camera, 20X optical zoom, 3G-SDI, HDMI, IP Streaming
	PT20X-USB-GY-G2		PT20X-USB-WH-G2	1080p PTZ camera, 20X optical zoom, USB3.0, HDMI, IP Streaming
	PT20X-ZCAM-G2			1080p Box Camera, 20X optical zoom, 3G-SDI, IP Streaming
	PTVL-ZCAM-G2			1080p Box Camera, Variable Lenses (4X included), 3G-SDI, IP Streaming

Control Accessories

	PT-BRDCSTR-(L,E,P)			Remote PTZ Head for handheld-broadcast cameras (3 models)
	DB9M-F-xx			Extension Cable, DB9M-F, Plenum, 4 lengths shown in ft. (xx=25, 50, 75, 100)
	VISCA-xx			Daisy Chain Cable, miniDIN8-MM, 4 lengths shown in ft. (xx=25, 50, 75, 100)
	HDSDI-xx			3G SDI Cable, BNC-MM, Plenum, 4 lengths shown in ft. (xx=25, 50, 75, 100)
	HC-JOY-G2			RS232, RS485, RS422, 3D Joystick and Keyboard, VISCA, Pelco-P, Pelco-D
	PT-JOY			IP control, 4D Joystick and Keyboard, Durable Metal Case

Mounting Accessories

	HCM-1-BK		HCM-1-WH	Small Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-2-BK		HCM-2-WH	Large Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-1C-WH			Small Open Ceiling Mount, mounts to 1"NPT pipe
	HCM-2C-WH			Large Open Base Ceiling Mount, mounts to 1"NPT pipe
	PT-CM-1-BK			Surface Ceiling Mount, mounts directly to ceiling or box w/ suppl. hardware

